

# COMMERCIAL INSTALLATION HOSE RETRIEVERS

### FOR USE WITH SINGLE HOSE WITH COUNTERWEIGHT

### STANDARD UNIT CONSISTS OF THE FOLLOWING:

- \* 18 MONTH LIMITED WARRANTY
- \* BALL BURNISHED ALUMINUM HEAD ASSEMBLY
- \* SELF-LUBRICATING BRONZE BUSHING IN SWIVEL-HEAD
- \* SELF-LUBRICATING BRONZE BUSHINGS ON ALL PULLEYS
- \*3/16" NYLON RETRACTOR ROPE-20' LONG
- \* SINGLE HOSE CLAMP
- \*COUNTERWEIGHT
- \*LONGER POST AVAILABLE IN 2" PIPE ONLY

CALIFORNIA STATE FIRE MARSHAL CERTIFICATION NUMBER: GVRC 005:024:2

## SINGLE PRODUCT HOSE, LESS POST

MODEL NO. DESCRIPTION 9901-3 5/8" X 15'-18' 9901-4 5/8° X 19'-22' 9901-5 5/8" X 23'-25' 9905-3 3/4" ¥ 15'-18' 9905-4 3/4" X 19'-22' 9905-5 3/4" X 23'-25' 9906-3 1" X 15'-18' 9906-4 1" X 19'-22 9906-5 1" X 23'-25' 1-1/4" X 15'-18' 9907-4 1-1/4" X 19'-22' 9907-5 1-1/4" X 23'-25' CUSTOMER TO SUPPLY

(FOR ROUND POST ONLY)

NOTE: ANCHOR COUPLING, RISER AND 2" ROUND POST FOR SWIVEL HEAD

IRWINDALE - CA

SWIVEL HEAD STYLE

CNI MFG

## **FIL-GUARD TANK BOTTOM PROTECTOR**

#### **SPECIFICATIONS:**


\*ONE PIECE HEAVY ALUMINUM CASTING FOR STRENGTH. ALL PRODUCT RESISTANCE RUBBER CUSHION 1/2" THICK. STAINLESS STEEL DROP TUBE ATTACHMENT BRACKET.

#### **FEATURES:**

- \* ATTACHES TO THE DROP TUBE WITH RIVETS TO ALLOW FOR REMOVAL FOR INSPECTION AND CLEANING.
- \* GRTAED OUTLET TO PREVENT RAGS OR PAPER FROM ENTERING THE TANK AND CLOGGING THE TURBINE MOTOR SUCTION LINE.
- \* RUBBER SHOCK ABSORBING DISC, 1/2" THICK AT BASE OF UNIT.
- \* A 3 1/2" TRAVEL ASSURES PROPER SEATING ON THE TANK BOTTOM.
- \* UPPER PORTION IS TAPERED OUT TOWARD THE SIDE OF THE TUBE TO PREVENT DAMAGE TO THE GAUGE STICK.
- \* AVAILABLE FOR A STANDARD OR COAXIAL 4" DROP TUBE.









9841